



# WIFI-Link Technologies Inc.



WEB: [www.wifi-link.com](http://www.wifi-link.com)

Service e-mail : [sales@wifi-link.com](mailto:sales@wifi-link.com)

## LP N MALE TO N FEMALE BULKHEAD 6GHz

### WL-LA-NP-NJBKD6G



The Lightning Surge Protectors listed on this page may also be referred to as: lightning suppressor, transient protector, spike arrestor, surge arrestor, lightning arrestor, spike protector, surge protector, lightning protector, spike suppressor, RF protector. Spelling of these products may also vary depending on location such as: lightning surge protector, RF protector, lightning suppresser, spike suppresser, spike arrester, surge arrester, and lightning arrester.

### Specifications:

Technical information	
➤ Frequency Range: 2 to 6GHz	➤ Breakdown Vo1 Tage Gas Tube Impules: $\leq 700V$
➤ VSWR: 1:1.7 Max	➤ Breakdown Vo1 Tage Gas Tube Insulation: $\geq 10000M\ \text{ohm}$
➤ Insertion Loss: 0.9 dB Max	➤ Resistance MAX withstand Current: 5KV
➤ Impedence: 50 ohm	➤ RF Power Rating: 15W
➤ Gas Tube DC: $230 \pm 20\%$	➤ Connector: N-type/Male to Female Bulkhead

