National Space Organization

Report No：FF141118E

Function Test Report

Lab. Director： Cheng Chun-Chi

Sign of Reporter： Yeh Chih-Hui

Report Date： Nov. / 25 / 2014

National Space Organization Antenna Measure Lab.
No.15, Prosperity 1st Road, Hsinchu Science Park,
Hsinchu 30078, Taiwan (R.O.C.)
TEL: 886-3-578-4208
FAX: 886-3-578-8062

Test Unit: Dual-Band Antenna **Model No:** 5dBi 白色雙頻天線 (2.4/5GHz) **Serial No:** WLD1-5024-05-03 **Received Date:** Nov./20/2014 **Total Page:** 17
Items to be measured: Antenna Gain / Antenna Pattern **Applicant:** WIFI-Link Technologies Co., Ltd. **Contact:** Zhi-juan Ze **Address:** No.25, Zhongyang Rd., Yongkang Dist., Tainan City 710, Taiwan (R.O.C.) **Tel:** 886-6-2523801 **Fax:** 886-6-2526033

I. Test Project

1. Test Date: Nov./21/2014 ~ Nov./24/2014
2. Test Method:
   - 2.1 The measurement only valid to the measured items. All of the measurement processes are certificated by ISO9001:2000 quality management.
   - 2.2 Test item, parameter setting and method are agreed by both sides. Test flow and test procedures are executed according to NSPO-PROC-0039.
   - 2.3 It is necessary to warm up the test facilities for at least one hour.
3. Test standard units:

Item	S/N	Valid date	Trace no.	Calibration Co.
Network Analyzer Agilent E8364B	MY43040631	2015/8/31	1-6182827751-1	Agilent Ltd.
Standard Horn Antenna	4101	2015/9/10	14-09-BCC-043-01	ETC

4. Test environment:

   Temperature: 21.3 ˚C Humidity: 50 %

5. Measured unit coordinate:



6. Reference Document:

   Antenna measurement system operation procedure, NSPO-PROC-0039, version: 0102, National Space Organization, 2012.



II. System parameter setup

A. Measure Surface

(I). Planer	□ Polar	□ Rectangular	□ Linear
(II). Spherical	□ E-th/E-phi	□ Co-pol/X-pol	
(III). Cylindrical	□ Y/Phi Vertical	□ X/Phi Horizontal	
(IV). Direct Far Field	■ E-th/E-phi	□ Co-pol/X-pol	

B. Probe type

Type: □ WG: _____ ■ Horn: X: 6.9 in Y: 6.1 in

C. AUT setup

(I). Orientation: Y

(II). Polarization: Linear

(III). AUT Probe Distance: 118.1 in

D. Frequency

Start: 2.40 GHz Stop: 2.50 GHz Step: 0.05 GHz

Start: 5.15 GHz Stop: 5.35 GHz Step: 0.10 GHz

Start: 5.82 GHz Stop: 5.83 GHz Step: 0.005 GHz

E. Sampling

I. Scan Priority	No of Theta (N):	201
	No of Phi Angles (M):	2
II. Travel Range	Theta (2-way) (deg):	360
	Phi-Cut (1/2 way)(deg):	180

III. Test Result

1. Antenna Gain

頻率	Gain H-Plane	Gain E-Plane
2.400 GHz	6.0 dBi	4.5 dBi
2.450 GHz	6.0 dBi	5.3 dBi
2.500 GHz	5.9 dBi	5.4 dBi
5.150 GHz	4.5 dBi	4.0 dBi
5.350 GHz	5.1 dBi	3.3 dBi
5.825 GHz	4.9 dBi	4.3 dBi

頻率	HPBW H-Plane	HPBW E-Plane
2.400 GHz	360.0 deg	30.6 deg
2.450 GHz	360.0 deg	35.2 deg
2.500 GHz	360.0 deg	35.3 deg
5.150 GHz	360.0 deg	26.5 deg
5.350 GHz	360.0 deg	26.7 deg
5.825 GHz	360.0 deg	43.2 deg

4. Antenna Pattern

ANTCOM

Far-Field Patterns
Frequency: 2.4000



Far-Field Patterns
Frequency: 2.4000



Far-Field Patterns
Frequency: 2.4500



Far-Field Patterns
Frequency: 2.4500



Far-Field Patterns
Frequency: 2.5000



Far-Field Patterns
Frequency: 2.5000



Far-Field Patterns
Frequency: 5.1500



Far-Field Patterns
Frequency: 5.1500



Far-Field Patterns
Frequency: 5.3500



Far-Field Patterns
Frequency: 5.3500



Far-Field Patterns
Frequency: 5.8250



Far-Field Patterns
Frequency: 5.8250