



# WIFI-Link™ Technologies Inc.

## 歲海尼可網路科技有限公司

WEB: <http://www.wifi-link.com.tw/> TEL: 06-2523801 FAX: 06-2526033

### LP N Female TO N Female 3GHz

### WL-LA-NJ-NJ3G



The Lightning Surge Protectors listed on this page may also be referred to as: lightning suppressor, transient protector, spike arrester, surge arrester, lightning arrester, spike protector, surge protector, lightning protector, spike suppressor, RF protector. Spelling of these products may also vary depending on location such as: lightning surge protector, RF protector, lightning suppresser, spike suppresser, spike arrester, surge arrester, and lightning arrester.

#### Specifications:

Technical information	
➤ Withstand voltage power: 125W	➤ Impedance: 50Ω
➤ V.S.W.R: ≤1.5	➤ Insertion Loss: ≤ 0.5 dB
➤ Pulse breakdown voltage: <600V (100V/s speed)	➤ Frequency range: DC 2500MHz
➤ AC current range: 20A	➤ Gap can: 1.5P
➤ Pulse current range: 200A	➤ DC breakdown voltage: 230 +/- 20% (100V/s speed)
➤ Overvoltage protection: >150V (100mA, <150ms)	➤ Connector: N male to N female
➤ Isolation resistor: 1000m ohms	➤ DC breakdown voltage: 230 +/- 20% (100V/s speed)

